



N SERIES / JAPANESE



LEOUYN
LEOUYN ENTERPRISE CO., LTD.

N SERIES (JAPANESE) SAFETY COUPLER



- One-push connection
- Safety design
- Compatible with N-Series plugs (N13, N12, N11, N10)



MODEL	Female Thread T	DIMENSIONS(mm)		
		L	H	A
N32-F2	1/8" PF	69.5	19	12
N32-F4	1/4" PF	69.5	19	14
N32-F6	3/8" PF	70.5	19	15
N32-F8	1/2" PF	72.5	22	16



MODEL	Male Thread T	DIMENSIONS(mm)			
		L	H	A	ØB
N32-M2	1/8" PT	71	19	10	5
N32-M4	1/4" PT	74	19	13	7
N32-M6	3/8" PT	75	19	14	8
N32-M8	1/2" PT	77	21	16	12



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N32-T4	1/4"	83.5	19	22.5	4
N32-T5	5/16"	83.5	19	22.5	7.5
N32-T6	3/8"	89.2	19	28.2	9
N32-T8	1/2"	92.5	19	31.5	9



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N32-H4	1/4"	89.5	19	28.5	4
N32-H5	5/16"	91	19	30	5
N32-H6	3/8"	92.5	19	31.5	7.5
N32-H8	1/2"	94	19	33	9




MODEL	Hose T	DIMENSIONS(mm)				
		L	H1	H2	A	ØB
N32-P4	4 x 6	73	19	12	12	4
N32-P5	5 x 8	76	19	14	15	7.5
N32-P6	6.5 x 10	79.5	19	16	18.5	9
N32-P8	8 x 12	78.5	19	19	17.5	9

N SERIES (JAPANESE) ONE-TOUCH COUPLER


- One-push connection
- Compatible with N-Series plugs (N13, N12, N11, N10)




MODEL	Female Thread T	DIMENSIONS(mm)		
		L	H	A
N21-F2	1/8" PF	49.3	19	12
N21-F4	1/4" PF	51.3	19	14
N21-F6	3/8" PF	55.3	21	15
N21-F8	1/2" PF	56.3	24	16





MODEL	Male Thread T	DIMENSIONS(mm)			
		L	H	A	ØB
N21-M2	1/8" PT	52.8	19	10	5
N21-M4	1/4" PT	55.8	19	13	7.5
N21-M6	3/8" PT	56.8	19	14	10.5
N21-M8	1/2" PT	58.8	21	16	12




MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N21-T4	1/4"	65.3	19	22.5	4
N21-T5	5/16"	65.3	19	22.5	6
N21-T6	3/8"	71	19	28.2	7.5
N21-T8	1/2"	74.3	19	31.5	9



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N21-H4	1/4"	71.3	19	28.5	4
N21-H5	5/16"	72.8	19	30	5
N21-H6	3/8"	74.3	19	31.5	7.5
N21-H8	1/2"	75.8	19	33	9



MODEL	Hose T	DIMENSIONS(mm)				
		L	H1	H2	A	ØB
N21-P2	4 x 6	54.8	19	12	12	3
N21-P4	5 x 8	57.8	19	14	15	4
N21-P6	6.5 x 10	61.3	19	16	18.5	5
N21-P8	8 x 12	60.3	19	19	17.5	6.5



N SERIES (JAPANESE) DUAL BALL-SWIVEL PLUG


- 360-degree rotation for maximum mobility
- Free rotation angle up to 54 degrees
- Dual swivel points for flexible movement
- Compatible with N-Series couplers (N32, N21)




MODEL	Female Thread T	DIMENSIONS(mm)		
		L	H	A
N13-F2	1/8" PF	69.6	19	12
N13-F4	1/4" PF	71.6	19	14
N13-F6	3/8" PF	72.6	21	15
N13-F8	1/2" PF	74.6	24	16.5




MODEL	Male Thread T	DIMENSIONS(mm)			
		L	H	A	ØB
N13-M2	1/8" PT	73.1	19	10	5
N13-M4	1/4" PT	76.1	19	13	7.5
N13-M6	3/8" PT	77.1	19	14	10.5
N13-M8	1/2" PT	79.1	21	16	12



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N13-T4	1/4"	85.6	19	22.5	4
N13-T5	5/16"	85.6	19	22.5	6
N13-T6	3/8"	91.3	19	28.2	7.5
N13-T8	1/2"	94.6	19	31.5	9



MODEL	Hose T	DIMENSIONS(mm)			
		L	H	A	ØB
N13-H4	1/4"	91.6	19	28.5	4
N13-H5	5/16"	93.1	19	30	6
N13-H6	3/8"	94.6	19	31.5	7.5
N13-H8	1/2"	96.1	19	33	9



MODEL	Hose T	DIMENSIONS(mm)				
		L	H1	H2	A	ØB
N13-P2	4 x 6	75.1	19	12	12	3
N13-P4	5 x 8	79.5	19	14	16.4	4
N13-P6	6.5 x 10	81.6	19	16	18.5	5
N13-P8	8 x 12	80.6	19	19	17.5	6.5

N SERIES (JAPANESE) BALL-SWIVEL PLUG


- 360-degree rotation
- Free rotation angle up to 27 degrees
- Single swivel point for smooth movement
- Compatible with N-Series couplers (N32, N21)




MODEL	Female Thread T	DIMENSIONS(mm)		
		L	H	A
N12-F2	1/8" PF	49.3	19	12
N12-F4	1/4" PF	51.3	19	14
N12-F6	3/8" PF	55.3	21	15
N12-F8	1/2" PF	56.3	24	16



MODEL	Male Thread T	DIMENSIONS(mm)			
		L	H	A	ØB
N12-M2	1/8" PT	52.8	19	10	5
N12-M4	1/4" PT	55.8	19	13	7.5
N12-M6	3/8" PT	56.8	19	14	10.5
N12-M8	1/2" PT	58.8	21	16	12



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N12-T4	1/4"	65.3	19	22.5	4
N12-T5	5/16"	65.3	19	22.5	6
N12-T6	3/8"	71	19	28.2	7.5
N12-T8	1/2"	74.3	19	31.5	9



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N12-H4	1/4"	71.3	19	28.5	4
N12-H5	5/16"	72.8	19	30	5
N12-H6	3/8"	74.3	19	31.5	7.5
N12-H8	1/2"	75.8	19	33	9



MODEL	Hose T	DIMENSIONS(mm)				
		L	H1	H2	A	ØB
N12-P2	4 x 6	54.8	19	12	12	3
N12-P4	5 x 8	57.8	19	14	15	4
N12-P6	6.5 x 10	61.3	19	16	18.5	5
N12-P8	8 x 12	60.3	19	19	17.5	6.5

N SERIES (JAPANESE) SWIVEL PLUG


- Smooth 360-degree parallel rotation for effortless operation
- Compatible with N-Series couplers (N32, N21)



MODEL	Female Thread T	DIMENSIONS(mm)		
		L	H	A
N11-F2	1/8" PF	46.7	17	12
N11-F4	1/4" PF	48.7	17	14
N11-F6	3/8" PF	50.7	21	15
N11-F8	1/2" PF	52.7	24	16.5




MODEL	Male Thread T	DIMENSIONS(mm)			
		L	H	A	ØB
N11-M2	1/8" PT	42.7	14	10	5
N11-M4	1/4" PT	45.7	14	13	7.5
N21-M6	3/8" PT	46.7	17	14	10.5
N11-M8	1/2" PT	48.7	21	16	12



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N11-T4	1/4"	55.2	15	22.5	4
N11-T5	5/16"	55.2	15	22.5	6
N11-T6	3/8"	60.9	15	28.2	7.5
N11-T8	1/2"	64.2	18	31.5	9



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N11-H4	1/4"	61.2	15	28.5	4
N11-H5	5/16"	62.7	15	30	6
N11-H6	3/8"	64.2	15	31.5	7.5
N11-H8	1/2"	65.7	18	33	9




MODEL	Hose T	DIMENSIONS(mm)				
		L	H1	H2	A	ØB
N11-P2	4 x 6	54	14	12	12	3
N11-P4	5 x 8	55	14	14	16.4	4
N11-P6	6.5 x 10	59	16	16	18.5	5
N11-P8	8 x 12	60	17	17	17.5	6.5

N SERIES (JAPANESE) STANDARD PLUG


- Compatible with N-Series couplers (N32, N21)





MODEL	Female Thread T	DIMENSIONS(mm)		
		L	H	A
N10-F2	1/8" PF	35	17	12
N10-F4	1/4" PF	36.5	17	14
N10-F6	3/8" PF	37.5	21	15
N10-F8	1/2" PF	40.5	24	16.5




MODEL	Male Thread T	DIMENSIONS(mm)			
		L	H	A	ØB
N10-M2	1/8" PT	37	14	10	5
N10-M4	1/4" PT	40	14	13	7.5
N10-M6	3/8" PT	41.5	17	14	10.5
N10-M8	1/2" PT	44.5	21	16	12




MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N10-T4	1/4"	49.5	15	22.5	4
N10-T5	5/16"	49.5	15	22.5	6
N10-T6	3/8"	55.2	15	28.2	7.5
N10-T8	1/2"	60	18	31.5	9



MODEL	Hose Barb T	DIMENSIONS(mm)			
		L	H	A	ØB
N10-H4	1/4"	53	15	28.5	4
N10-H5	5/16"	57	15	30	6
N10-H6	3/8"	59	15	31.5	7.5
N10-H8	1/2"	60.5	18	33	9



MODEL	Hose T	DIMENSIONS(mm)				
		L	H1	H2	A	ØB
N10-P2	4 x 6	38.5	14	12	12	3
N10-P4	5 x 8	43.9	14	14	16.4	4
N10-P6	6.5 x 10	46	16	16	18.5	5
N10-P8	8 x 12	45	17	17	17.5	6.5





LEOUYN

LEOU YN ENTERPRISE CO., LTD.(AURAX)

Vat NO. 89349123

Tel +886-6-5713379

Web www.leouyn-coupler.com.tw

Fax +886-6-5722299

Mail service@leouyn-coupler.com.tw

Address No. 5-5, Liaozi bu, Madou Dist., Tainan City 721, Taiwan



WEB



LINE



WHATSAPP